



NOTES:

1. MATERIAL: .012 - .025 THICK PHOTO-SENSITIZED ALUMINUM ALLOY, BACKED WITH PRESSURE SENSITIVE ADHESIVE PER MIL-P-15024, TYPE H; PRESSURE SENSITIVE ADHESIVE TO BE BLACK.
2. BORDER, SERIAL NO. BLOCK AND CHARACTERS TO BE FROSTED ALUMINUM, BACKGROUND TO BE BLACK.
3. LETTERS SHALL BE GOTHIC OR FUTURA CAPITALS (SANS-SERIFS); NUMBERS SHALL BE ARABIC, LETTERS AND NUMBERS SHALL BE .09 HIGH UNLESS OTHERWISE SPECIFIED.
4. MARK '80063-A3007756' ON PAPER BACKING ON REAR OF PLATE, .10 HIGH CHARACTERS, BLACK, PER MIL-M-13231, GROUP II.
5. SERIAL NO. TO BE MARKED WITH .06 HIGH CHARACTERS.
6. WORKMANSHIP PER REQUIREMENT 9 OF MIL-STD-454 SHALL APPLY.
7. CHARACTERS SHALL BE SYMMETRICALLY POSITIONED AS SHOWN.
8. DIMENSIONS FOR SERIAL NO. BLOCK TO BE .38 LONG, .09 HIGH.
9. DIMENSIONAL DATA IS BASED ON AMERICAN NATIONAL STANDARD ANSI Y14.5-1973